

Hybrid Inverter

LXP-LB-US 12kW

LXP-LB-EU 12kW

- 12kW EPS Output
- 10 units Paralleling
- AC Coupling Function
- 3 MPPT Input for max input 18kW
- Separated Generator Input
- 200A AC Passthrough Current
- PV Module Monitoring
- Peak Shaving Function
- Color LCD, Touch Screen



LU X POWER TEK

Specification

Your Reliable
Energy Solution
Partner

Battery Parameters	LXP-LB 12K
Compatible Battery Type	Lead-acid/Lithium
Nominal Battery Voltage	48V
Battery Voltage Range	40V~60V
Maximun Charging/Discharging Current	250A/250A
Maximun Charging/Discharging Power	12000W
Input DC(PV Side)	
Max. DC Input Power for Single MPPT	12000W/7000W/7000W
Max. PV Input Power	18000W
DC Input Voltage Range	100V~600V
Nominal DC Input Voltage	360V
Full Power MPPT Voltage Range	230~500V
Max. DC Input Current	25A/15A/15A
MPPT Number/(Strings per MPPT)	3(2/1/1)
Output/Inout AC(Grid)	
Nominal Power	12000W
Nominal AC Voltage	240V 208V
Operating Voltage Range	180V~270V
Max. Continuous AC Current	50A@240V 50A@208V
Nominal AC Frequency	50Hz/60Hz
UPS Output-with Battery	
UPS Max. Output Power	12000W
	240V 208V
UPS Nominal Output Voltage	120V/240V 120V/208V
	50Hz/60Hz
UPS Nominal Output Frequency	50A@240V 57.7A@208V
UPS Nominal Output Current	14kW 10minutes / 16kW 5minutes / 20kW 500ms
Peak Power	<20ms
Switching Time	
Efficiency	
MPPT Efficiency	99.9%
Max. Efficiency	97.5%
EU Efficiency	96.5%
Battery Charging Efficiency	95%
Battery Discharging Efficiency	94.5%
Protection	
Anti-islanding Protection	YES
DC Switch	YES
Ingress Protect Degree	IP65
SPD Protection	YES
AFCI	OPT
RSD	OPT
General Data	
Dimension(mm)	670*490*265
Weight	42kg
Display	Color LCD
Topology	Transformer-less
Ambient Temperature Range	-25~60℃
Cooling	FAN
Communication	RS485/Wi-Fi/CAN
Standard & Certification	
EMC	IEEE1547 FCC SDOC
Safety Standard	UL 1741
Grid Standdards	IEEE1547

